

NEW TECHNOLOGY

MJ-DB3200&5000PRO With 24-36pcs Konica 1024i/1024A



Intelligent constant temperature water cooling variable frequency adsorption platform




Super quiet machine-Imported guiderrail with magnetic levitation



Printing color without any deviation also high saturation



All in one computer built-in printer with handle remote control operation



Unlock new profit opportunities with double-sided printing capabilities



Printhead Resolution

Konica1024i

	2*CMYK 8 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>60m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	60m ² /h	1016x720	6pass	45m ² /h	1016x1080		2*CMYK W 10 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>60m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	60m ² /h	1016x720	6pass	45m ² /h	1016x1080
		Print Speed	DPI																		
	4pass	60m ² /h	1016x720																		
	6pass	45m ² /h	1016x1080																		
		Print Speed	DPI																		
	4pass	60m ² /h	1016x720																		
	6pass	45m ² /h	1016x1080																		
		3*CMYK 12 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m ² /h	1016x720	6pass	65m ² /h		1016x1080		3*CMYK LC LM 18 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m ² /h	1016x720	6pass
		Print Speed	DPI																		
4pass	80m ² /h	1016x720																			
6pass	65m ² /h	1016x1080																			
	Print Speed	DPI																			
4pass	80m ² /h	1016x720																			
6pass	65m ² /h	1016x1080																			
	4*CMYK LC LM 24 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>100m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>85m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	100m ² /h	1016x720	6pass	85m ² /h	1016x1080		3*CMYK W 15 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m ² /h	1016x720	6pass	65m ² /h	1016x1080
		Print Speed	DPI																		
4pass	100m ² /h	1016x720																			
6pass	85m ² /h	1016x1080																			
	Print Speed	DPI																			
4pass	80m ² /h	1016x720																			
6pass	65m ² /h	1016x1080																			
	6*CMYK 24 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>180m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>108m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	180m ² /h	1016x720	6pass	108m ² /h	1016x1080		6*CMYK LC LM 36 pcs <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>180m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>108m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	180m ² /h	1016x720	6pass	108m ² /h	1016x1080
	Print Speed	DPI																			
4pass	180m ² /h	1016x720																			
6pass	108m ² /h	1016x1080																			
	Print Speed	DPI																			
4pass	180m ² /h	1016x720																			
6pass	108m ² /h	1016x1080																			

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 3 rows, match all production need		
Machine Functions	UV double side printing, Lack ink alarm, Anti-collusion device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Print Colors	CMYK LC LM W W
Printing Heads	24-36pcs Konica 1024i/1024A	Working Environment	6000W Electricity Power, 20°C-28°C humidty40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, Industrial feeding&take-up system, All-In-One Computer(optional)	Package Info	5950*2670*2350mm,5000KG