

NEW DESIGN

MJ-HD2500PRO

With 2-18pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



Auto Anti-collision System to avoid damage



Independent constant temperature heating control ink supply system



None after-service negative Ink supply system



Printing material automatic height detection device



Using domestic BYHX in the forefront of inkjet printing control system





Printhead Resolution

Konica1024i

Konica1024i	 <p>1*CMYK 4 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>33m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>25m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	33m ² /h	1016x720	6pass	25m ² /h	1016x1080
		Print Speed	DPI							
	4pass	33m ² /h	1016x720							
	6pass	25m ² /h	1016x1080							
	 <p>2*CMYK 8 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>48m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>36m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	48m ² /h	1016x720	6pass	36m ² /h	1016x1080
	Print Speed	DPI								
4pass	48m ² /h	1016x720								
6pass	36m ² /h	1016x1080								
 <p>2*CMYK+2W 10 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>47m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>35m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	47m ² /h	1016x720	6pass	35m ² /h	1016x1080	
	Print Speed	DPI								
4pass	47m ² /h	1016x720								
6pass	35m ² /h	1016x1080								
 <p>3*CMYK 12 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>68m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	68m ² /h	1016x720	6pass	45m ² /h	1016x1080	
	Print Speed	DPI								
4pass	68m ² /h	1016x720								
6pass	45m ² /h	1016x1080								
 <p>2*CMYK LC LM W 14 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>47m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>35m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	47m ² /h	1016x720	6pass	35m ² /h	1016x1080	
	Print Speed	DPI								
4pass	47m ² /h	1016x720								
6pass	35m ² /h	1016x1080								

RICOH G5/G6

RICOH G5/G6	 <p>1*CMYK W 3 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>28m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>21m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	28m ² /h	720x600	6pass	21m ² /h	720x900
		Print Speed	DPI							
	4pass	28m ² /h	720x600							
	6pass	21m ² /h	720x900							
	 <p>1*CMYK W V 4 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>27m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>20m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	27m ² /h	720x600	6pass	20m ² /h	720x900
	Print Speed	DPI								
4pass	27m ² /h	720x600								
6pass	20m ² /h	720x900								
 <p>2*CMYK+1W 5 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>40m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>33m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	40m ² /h	720x600	6pass	33m ² /h	720x900	
	Print Speed	DPI								
4pass	40m ² /h	720x600								
6pass	33m ² /h	720x900								
 <p>3*CMYK 6 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>55m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>42m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	55m ² /h	720x600	6pass	42m ² /h	720x900	
	Print Speed	DPI								
4pass	55m ² /h	720x600								
6pass	42m ² /h	720x900								
 <p>3*CMYK+2W 8 pcs</p> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>55m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>42m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	55m ² /h	720x600	6pass	42m ² /h	720x900	
	Print Speed	DPI								
4pass	55m ² /h	720x600								
6pass	42m ² /h	720x900								

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 4 rows, match all production need	Print Colors	CMYK LC LM W V
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collision device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Working Environment	5000W Electricity Power, 20°C-28°C humidty40%-70%
Printing Heads	2-18pcs Ricoh Gen5/Gen6/Konica 1024i /Konica 1024A	Package Info	4626*1550*1600mm,2500KG
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)		