

**NEW DESIGN**

**MJ-HD6600PRO**

With 8-40 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A




Adapt to different diameter material by adjusting air pressure inside rollers



Branded accessories used for high attrition areas



Integrated Big functional machine control centre for high-efficiency



Rigorous ink filtration design effectively avoid impurities from going into the ink supply system



Support max 40 or more OEM konica printheads with higher speed



**Printhead Resolution**

Konica1024i

	<b>2*CMYK</b> <span style="float: right;">8 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>60m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	60m <sup>2</sup> /h	1016x720	6pass	45m <sup>2</sup> /h	1016x1080		<b>2*CMYK W</b> <span style="float: right;">10 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>60m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	60m <sup>2</sup> /h	1016x720	6pass	45m <sup>2</sup> /h	1016x1080
		Print Speed	DPI																		
	4pass	60m <sup>2</sup> /h	1016x720																		
	6pass	45m <sup>2</sup> /h	1016x1080																		
		Print Speed	DPI																		
	4pass	60m <sup>2</sup> /h	1016x720																		
	6pass	45m <sup>2</sup> /h	1016x1080																		
		<b>3*CMYK</b> <span style="float: right;">12 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m <sup>2</sup> /h	1016x720	6pass	65m <sup>2</sup> /h		1016x1080		<b>3*CMYK LC LM</b> <span style="float: right;">18 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m <sup>2</sup> /h	1016x720	6pass
		Print Speed	DPI																		
4pass	80m <sup>2</sup> /h	1016x720																			
6pass	65m <sup>2</sup> /h	1016x1080																			
	Print Speed	DPI																			
4pass	80m <sup>2</sup> /h	1016x720																			
6pass	65m <sup>2</sup> /h	1016x1080																			
	<b>4*CMYK LC LM</b> <span style="float: right;">24 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>100m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>85m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	100m <sup>2</sup> /h	1016x720	6pass	85m <sup>2</sup> /h	1016x1080		<b>3*CMYK W</b> <span style="float: right;">15 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>80m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>65m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	80m <sup>2</sup> /h	1016x720	6pass	65m <sup>2</sup> /h	1016x1080
		Print Speed	DPI																		
4pass	100m <sup>2</sup> /h	1016x720																			
6pass	85m <sup>2</sup> /h	1016x1080																			
	Print Speed	DPI																			
4pass	80m <sup>2</sup> /h	1016x720																			
6pass	65m <sup>2</sup> /h	1016x1080																			
	<b>6*CMYK</b> <span style="float: right;">24 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>180m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>108m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	180m <sup>2</sup> /h	1016x720	6pass	108m <sup>2</sup> /h	1016x1080		<b>6*CMYK LC LM</b> <span style="float: right;">36 pcs</span> <table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>180m<sup>2</sup>/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>108m<sup>2</sup>/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	180m <sup>2</sup> /h	1016x720	6pass	108m <sup>2</sup> /h	1016x1080
	Print Speed	DPI																			
4pass	180m <sup>2</sup> /h	1016x720																			
6pass	108m <sup>2</sup> /h	1016x1080																			
	Print Speed	DPI																			
4pass	180m <sup>2</sup> /h	1016x720																			
6pass	108m <sup>2</sup> /h	1016x1080																			

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 6 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collision device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Print Colors	CMYK LC LM W V
Printing Heads	8-40pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A	Working Environment	6000W Electricity Power, 20°C-28°C humidty40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYXH Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	9490*2195*1785mm,5000KG